



TECHNICAL DATA SHEET

MultiFix ProPutty

MultiFix ProPutty is a hand kneadable, speciality epoxy putty that can be used to permanently repair many different substrates. It will bond fibreglass, metals, wood, concrete and glass and can even be applied under water. It is suitable for repairing leaking tanks and drums, patching holes in pipes, stopping leaks, repairing cracks and holes in concrete and brickwork. Pro Putty will harden in 10 mins, repair item can be back in service in 1 hour and will reach full strength in 24hrs.

Directions for use: Lightly abrade parts to be bonded, filled or repaired. Ensure the parts are, dry, clean and free from dirt, oil or grease. Cut epoxy stick to size and hand roll/knead the putty until it is an even grey colour. Firmly apply to substrate, pushing and moulding to shape. Smooth any edges with a wetted finger or knife.

<u>PROPERTIES</u> Resin Colour Viscosity	Metal epoxy putty Black - changes to grey after mixing putty/hand kneadable
<u>CURING</u> Handling bond Chemical Cure Full Strength	5-10 minutes 1 hour 24 hours
<u>TEMPERATURE RESISTANCE</u> Temperature wet Temperature dry	49°C 121°C
<u>STRENGTH</u> Adhesive tensile shear Comprehensive strength Cured hardness shore D	5 N/mm ² 83 N/mm ² 75
<u>CURED PROPERTIES</u> High Damp and humidity resistance Chemical resistance	Excellent -can be applied to wet surfaces. Very good - not recommended for full immersion applications

Issued 09.12.14

Page 1 of 1