



Bonham Drive, Eurolink Industrial Estate
 Sittingbourne, Kent ME10 3RY
 enquires@eurobond-adhesives.co.uk
 www.multifixadhesive.com
 +44 (0)1795 427888

TECHNICAL DATA SHEET

MultiFix Bearing Fit Adhesive

MultiFix Bearing Fit is a single part medium strength anaerobic securing compound, designed for fitting cylindrical metal assemblies such as bearings & shafts which will require disassembly in the future. Bearing Fit has a static shear strength of 12N/mm².

<p><u>INSTRUCTIONS FOR USE</u> Ensure parts are clean, dry and free from oil and grease.</p>	
<p><u>PROCEDURE FOR APPLICATION</u> Product is normally hand applied from the bottle.</p>	
<p><u>STORAGE</u> Store in a cool area out of direct sunlight. Shelf Life > 12 months @ 20°C</p>	
<p><u>HEALTH & SAFETY IN USE</u> IRRITANT Contains Methacrylate Esters, Irritates eyes, the respiratory organs and the skin. In case of contact with the skin wash immediately with plenty of water.</p>	
<p><u>TECHNICAL FEATURES</u> Resin Colour Fixture Speed No Activator Fixture Speed with Activator Viscosity Gap fill Flashpoint Shelf Life Specific Gravity Max Operating Temperature</p>	<p>Mod. Dimethacrylate Yellow 10-15 mins <5 mins 1500 cps 0.2 mm >100°C 12 month 1.06 -55°C to + 150°C</p>
<p><u>CURED PERFORMANCE</u> Full Cure Time Static Shear Strength Iso 10123 pin/collars range</p>	<p>12 hours 12N/mm² 1 – 16 N/mm⁽²⁾</p>

PRESENTATION

MultiFix Bearing Fit is available in 50ml

Issued 15.01.16

Page 2 of 2