



**TECHNICAL DATA SHEET**

**MultiFix Hydraulic Line Sealer**

**MultiFix Hydraulic Line Sealer EBA542** is a tough high pressure seal used on all types of threaded couplings on low, medium and high pressure lines. EBA542 is ideally suited to fit valves, threaded couplings, adaptors, quick disconnect parts, compression fittings and vibration proofing joints.

<p><b><u>USEFUL NOTES</u></b>          For fast cure, clean parts and apply local heat to joints with a heat gun or soft flame.</p>	
<p><b><u>PROPERTIES</u></b>          EBA542 is tolerant of a light oil film. Seals up to 400 bar, 20mm fittings. Vibration proofs joints. Easily dismantled with tools.</p>	
<p><b><u>INSTRUCTION FOR USE</u></b>          Ensure parts are clean, dry and free from oil and grease.  <b><u>STORAGE</u></b>          Store in a cool area out of direct sunlight.          Shelf life 1 year @ 20°C  <b><u>HEALTH &amp; SAFETY IN USE</u></b>  <b><u>IRRITANT</u></b>          Contains Methacrylate Esters and some products contain small amounts of Acrylic Acid. Irritates eyes, the respiratory organs and the skin. In case of contact with the skin was immediately with plenty of water.  <b><u>TECHNICAL FEATURES</u></b>          Resin          Colour          Fixture Speed No Activator (see chart)          Fixture Speed with Activator (see chart)          Spindle 2 @ 2.5 rpm          Spindle 2 @ 20 rpm          Gap fill          Flashpoint          Shelf Life          Specific Gravity          Max Operating Temperature</p>	<p>Dimethacrylate          Brown          10-20 mins          &lt;5 mins          1000 to 2750 cps          400 to 800 cps          0.05mm to 0.25 mm          &gt;100°C          1 Years @ 20°C          1.06          -55°C to + 150°C</p>

<p><b><u>CURED PERFORMANCE</u></b></p> <p>Full Cure  Typical breakaway ISO 10964  Typical prevailing ISO 10964  DIN 10964 Breakloose  DIN 10964 Prevailing  Typical Break and Prevailing</p>	<p>12 hours  15 N.m  &gt;8 N.m  24 N.m  15 to 35 N.m  20N.m/15N.m</p>
<p><b><u>PRESENTATION</u></b></p> <p>MultiFix Hydraulic Line Sealer is available in 50ml.</p>	

**Issued 15.01.16**

**Page 2 of 2**